

Torque Settings:

Main Bearing Stud Ø 8.....	1.8	kgm	1.8	kgm
Main Bearing Stud Ø 12.....	3.5	kgm	3.5	kgm
Main Bearing Nuts Ø 8.....	2.8	kgm	2.8	kgm
Main Bearing Nuts Ø 12.....	9	kgm	9	kgm
Cylinder Head Studs.....	3	kgm	3	kgm
Cylinder Head Nuts.....	8.6	kgm	8.6	kgm
Connecting Rod Bolts.....	6	kgm	6	kgm
Crankshaft Flywheel Bolts.....	2.8	kgm	2.8	kgm
Clutch Plate Bolts.....	2.8	kgm	2.8	kgm
Camshaft Support Nuts.....	2.8	kgm	2.8	kgm
Inlet & Exhaust Manifold Bolts.....	3	kgm	3	kgm
Crown & Carrier Bolts.....	9	kgm	9	kgm
Output Shaft Nut.....	14	kgm	14	kgm
Rear Axle Shaft.....	19	kgm	19	kgm
Drive Shaft Clamping.....	3	kgm	3	kgm
Rear Brake & Handbrake Caliper Clamping.....	8	kgm	8	kgm
Front Brake Caliper Clamping.....	8	kgm	8	kgm
Cam Gear Nut.....	8.5	kgm	8.5	kgm
Front Pully Bolts.....	2.8	kgm	2.8	kgm
Wheel Nuts.....	13	kgm	13	kgm
Wheel Hub Nuts.....	17	kgm	17	kgm
Lower Swivel Pin Bolt.....	12	kgm	12	kgm

Sizes:

Length.....	4140	mm	4140	mm
Width.....	1890	mm	2000	mm
Height.....	1070	mm	1070	mm
Rack.....	2450	mm		
Front Track.....	1520 (Track)	mm	1492	mm
Rear Track.....			1606	mm
Weight.....	1065	kg.	1490	kg.